

Safety Data Sheet

BOSS® 336 Extreme Weather Foam Gun Grade

Section 1. Identification

| Product Identifier Synonyms Manufacturer Stock Numbers | BOSS® 336 Extreme We 33624 04405TN10 | ather Foam Gun Grade | |
|---|---|---|-----------------------|
| Recommended use Uses advised against | Refer to Technical Inform Refer to Technical Inform | | |
| Manufacturer Contact Address | Soudal Accumetric 350 Ring Road Elizabethtown, KY, 42701 USA | | |
| | Phone (270) 769-3385 | Emergency Phone (800) 424-9300 CHEMTREC | Fax (270) 765-2412 |

Section 2. Hazards Identification

| Classification | ACUTE TOXICITY - DERMAL - Category 4 ACUTE TOXICITY - INHALATION - Category 4 ACUTE TOXICITY - ORAL - Category 4 CARCINOGENICITY - ORAL - Category 2 EYE DAMAGE/IRRITATION - Category 2A FLAMMABLE AEROSOLS - Category 1 SENSITIZATION - RESPIRATORY - Category 1A SENSITIZATION - SKIN - Category 1 SKIN CORROSION/IRRITATION - Category 2 SPECIFIC TARGET ORGAN TOXICITY (Repeated Exposure) - Category 2 SPECIFIC TARGET ORGAN TOXICITY (Single Exposure) - Category 3 |
|----------------|---|
| Signal Word | Danger |

| Pictogram | |
|--------------------------|--|
| Hazard Statements | Causes serious eye irritation Causes skin irritation Extremely flammable aerosol Harmful if inhaled Harmful if swallowed Harmful in contact with skin May cause allergy or asthma symptoms or breathing difficulties if inhaled May cause an allergic skin reaction May cause damage to organs through prolonged or repeated exposure (respiratory tract). May cause respiratory irritation. Suspected of causing cancer. |
| Precautionary Statements | |
| Response | Call a poison center/doctor if you feel unwell. Get medical advice/attention if you feel unwell. If experiencing respiratory symptoms: Call a poison center/doctor. If exposed or concerned: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing. If on skin: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. If swallowed: Call a poison center/doctor if you feel unwell. Read label before use. If medical advice is needed, have product container or label at hand. Rinse mouth. Wash contaminated clothing before reuse. |
| Prevention | Avoid breathing dust/fume/gas/mist/ vapors/spray. Contaminated work clothing must not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Do not handle until all safety precautions have been read and understood. Do not spray on an open flame or other ignition source. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Obtain special instructions before use. Pressurized container: Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. |
| Storage | Protect from sunlight. Do not expose to temperatures exceeding 50C/122F. Store in a well-ventilated place. Keep container tightly closed. Store locked up. |

| Disposal | Dispose of contents/container to in accordance with local/regional/national /international regulations. |
|-------------------------------------|--|
| Ingredients of unknown toxicity | 0% |
| Hazards not Otherwise Classified | |
| Other Hazards | Contains isocyanates. See information supplied by the manufacturer. Allergic sensitization may be possible with isocyanates. Persons already sensitized to diisocyanates may develop allergic reactions when using this product. |

| Section 3. Ingredients | | |
|------------------------|---|-----------|
| CAS | Ingredient Name | Weight % |
| 6425-39-4 | Morpholine, 4,4'-(oxydi-2,1-ethanediyl)bis- | < 1 % |
| 75-28-5 | Isobutane | < 10 % |
| 9016-87-9 | Polymeric diphenylmethane diisocyanate | > 25 % |
| 74-98-6 | Propane | 1% - 5% |
| | Coploymer | 1% - 5% |
| 8001-20-5 | Tung oil | 10% - 15% |
| 115-10-6 | Dimethyl ether | 10% - 15% |
| 13674-84-5 | Trichorylpropylene Phophate | 25% - 30% |

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-Aid Measures

| Description of necessary measures | IF exposed or concerned: Get medical advice/attention; Call a POISON CENTER or doctor/physician. Get medical advice/attention if you feel unwell. |
|--|---|
| Inhalation | IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician. Specific treatment (see label). If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: |
| Skin | IF ON SKIN: Wash with plenty of soap and water. Call a POISON CENTER or doctor/physician if you feel unwell. Specific treatment (see on this label). Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. |
| Eyes | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. |
| Ingestion | IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. Rinse mouth. |
| Indication of any immediate medical attention and special treatment needed | e Treat symptomatically and supportively. Persons already sensitized to diisocyanates may develop allergic reactions when using this product. |

Most Important Symptoms/Effects Acute

Harmful if swallowed. Harmful in contact with skin. Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation.

Delayed

May cause allergic or asthmatic symptoms or breathing difficulties if inhaled. May cause allergic skin reaction. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure: respiratory tract.

Section 5. Fire Fighting Measures

| Suitable Extinguishing Media | Water, carbon dioxide |
|---|--|
| Unsuitable Extinguishing Media | None known |
| Special Hazards Arising from the Chemical | Extremely flammable aerosol. |
| Hazardous Combustion Products | Oxides of carbon, Phosphorus oxides, hydrogen cyanide, hydrogen chloride. May polymerize when heated. |
| Special Protective Equipment and Precautions for Firefighters | Keep away from heat, sparks, open flame, and hot surfaces - No smoking. Do not spray on an open flame or other ignition sources. Do not pierce or burn, s even after use. Wear full protective fire fighting gear including self contained breathing apparatus (SCBA) for protection against possible exposure. |
| Fire Fighting Measures | Danger of explosion. Keep unnecessary people away, isolate hazard area and deny entry. Cool containers with water from unmanned hose holder or monitor nozzles until well after fire is out. Do not allow to enter into surface water or drains. |

Section 6. Accidental Release Measures

| Personal Precautions, | Wear appropriate personal protective equipment recommended in Section 8 |
|---------------------------|---|
| Protective Equipment and | of the SDS. Do not smoke when using this product or handle near an open |
| Emergency Procedures | flame or sparks. Use explosion-proof electrical/ventilating/lighting equipment. |
| Methods and Materials for | Do not pierce or burn, even after use. |
| Containment and Cleaning | |
| Up | |

Environmental Precautions Do not allow to enter into surface water or drains. Dike for later disposal.

Section 7. Handling and Storage

Precautions for Safe Handling Keep away from heat, sparks, open flame, and hot surfaces - No smoking. Do not spray on an open flame or other ignition sources. Do not pierce or burn, even after use. Wash thoroughly after handling. Do not eat, drink, or smoke when using this product. Wear protective gloves/clothing and eye/face protection. Take off contaminated clothing and wash before re-use. Contaminated work clothing should not be allowed out of the workplace. Do not breathe dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. [In case of inadequate ventilation] wear respiratory protection. Obtain special instructions before use. Do not handle until all

| | safety precautions have been read and understood. Use explosion-proof electrical/ventilating/lighting equipment. |
|------------------------|--|
| Conditions for Safe | Store in a well-ventilated place. Keep container tightly closed. |
| Storage, Including any | Store locked up. |
| Incompatibilities | Protect from sunlight. Do not expose to temperatures exceeding 50C/122F. Ensure adequate ventilation of the storage area. Maximum storage period (time): 1 year. |
| Incompatible Materials | Heat, strong acids, strong bases, Amines. Keep away from all ignition sources. |

Section 8. Exposure Controls/Personal Protection

| Occupational Exposure Limits | Ingredient Name | ACGIH TLV | OSHA PEL | STEL |
|--|---|-----------------|-----------------|-------------|
| | Morpholine, 4,4'-(oxydi- 2,1-ethanediyl)bis- | N/A | N/A | N/A |
| | Isobutane | 1000 ppm | N/A | 1000 ppm |
| | Polymeric diphenylmethane diisocyanate | 0.005 ppm | 0.02 mg/m≈ | N/A |
| | Propane | 1000 ppm TWA | 1000 ppm PEL | N/A |
| | Coploymer | N/A | N/A | N/A |
| | Tung oil | N/A | N/A | N/A |
| | Dimethyl ether | N/A | 400 ppm | N/A |
| | Trichorylpropylene Phophate | N/A | N/A | N/A |
| Personal Protective Equipment Component Exposure Limits | Goggles, Gloves Propane (74-98-6) ACGIH: 1000 ppm TWA NIOSH: 1000 ppm TWA; 1800 mg/m3TWA 2100 ppmIDLH (10% LEL) OSHA (US): | | | |
| | Isobutane (75-28-5) ACGIH: 1000 ppm STEL NIOSH: 800 ppmTWA; 1900 mg/m3TWA Dimethyl ether (115-10-6) Europe: | | | |

| | 1000 ppm TWA; 1920 mg/m3 TWA |
|--|---|
| Biological limit value | There are no biological limit values for any of this product's components. |
| Engineering Controls | Use explosion-proof electrical/ventilating/lighting equipment. Keep away from heat/sparks/open flames/hot surfaces. |
| Individual Protection | Eye/face protection |
| Measures, such as Personal Protective | Wear splash resistant safety goggles. |
| Equipment | Skin Protection |
| | Wear suitable protective clothing and gloves. |
| | Respiratory Protection |
| | Use a respirator with an organic vapor cartridge for concentrations exceeding the occupational exposure limit. |
| | Glove Recommendations |

Recommended material type: LOW DENSITY POLYETHYLENE

Section 9. Physical and Chemical Properties

| Physical State | Aerosol |
|---------------------------------------|----------------|
| Color | Champagne |
| Odor | Characteristic |
| Odor Threshold | Not available |
| | Soluble in |
| Solubility | organic |
| | solvents |
| Partition coefficient Water/n-octanol | Not available |
| VOC% | N/A |
| Viscosity | Not available |
| Specific Gravity | 0.95 |
| Density lbs/Gal | 7.928 |
| Pounds per Cubic Foot | 59.307 |
| Flash Point | Not available |
| FP Method | N/A |
| Ph | Not available |
| Melting Point | Not available |
| Boiling Point | Not available |
| Boiling Range | Not available |
| LEL | N/A |
| UEL | N/A |
| Evaporation Rate | Not available |
| Flammability | Not available |
| Decomposition Temperature | Not available |
| Auto-ignition Temperature | Not available |
| Vapor Pressure | Not available |
| Vapor Density | Not available |

Note

The above information is not intended for use in preparing product

specifications. Contact Soudal Accumetric before writing specifications.

Section 10. Stability and Reactivity

| Reactivity | May polymerize when heated. |
|---------------------------------------|---|
| Chemical Stability | Stable under normal conditions of use. |
| Possibility of Hazardous Reactions | May polymerize when heated. |
| Conditions to Avoid | Avoid contact with incompatible materials. Keep away from heat/sparks/open flame/hot surfaces - No smoking. Do not spray on an open flame or other ignition sources. Do not pierce or burn, even after use. |
| Incompatible Materials | Heat, strong acids, strong bases, Amines, Keep away from all ignition sources. |
| Hazardous decomposition products | Oxides of carbon, Phosphorus oxides, hydrogen cyanide, hydrogen chloride. |

Section 11. Toxicological Information

| Information on Likely Routes of Exposure | Inhalation Harmful if inhaled. May cause allergic or asthmatic symptoms or breathing difficulties if inhaled. May cause respiratory irritation. |
|---|--|
| | Skin Contact Harmful in contact with skin. Causes skin irritation. May cause allergic skin reaction. |
| | Eye Contact Causes serious eye damage. |
| | Ingestion Harmful if swallowed. |
| Component Analysis - LD50/LC50 | The components of this material have been reviewed in various sources and the following selected endpoints are published: 2-Propanol, 1-chloro-, phosphate (3:1) (13674-84-5) Oral LD50Rat 500 mg/kg Dermal LD50Rabbit 1230 mg/kg Inhalation LC50Rat 5 mg/L 4 h |
| | Isocyanic acid, polymethylenepolyphenylene ester (9016-87-9) Inhalation LC50Rat 490 mg/m3 4 h |
| | Propane (74-98-6) Inhalation LC50Rat 658 mg/L 4 h |
| | Isobutane (75-28-5) Inhalation LC50Rat 658 mg/L 4 h |
| | Dimethyl ether (115-10-6) Inhalation LC50Rat 308.5 mg/L 4 h |

| Acute and Chronic Toxicity | Immediate Effects Harmful if swallowed. Harmful in contact with skin. Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. May cause allergic or asthmatic symptoms or breathing difficulties if inhaled. May cause respiratory irritation. |
|--|--|
| | Delayed Effects Suspected of causing cancer. May cause allergic skin reaction. May cause damage to organs through prolonged or repeated exposure: respiratory tract. |
| Irritation/Corrosivity Data | Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. |
| Respiratory Sensitization | May cause allergic or asthmatic symptoms or breathing difficulties if inhaled. |
| Dermal Sensitization | May cause allergic skin reaction. |
| Component Carcinogenicity | Isocyanic acid, polymethylenepolyphenylene ester (9016-87-9) IARC: |
| | Supplement 7 [1987]; Monograph 19 [1979](Group 3 (not classifiable)) DFG: |
| | Category 4 (no significant contribution to human cancer) |
| Germ Cell Mutagenicity | No data available |
| Reproductive Toxicity | No data available |
| Specific Target Organ Toxicity | Single Exposure: respiratory tract. Repeated Exposure: respiratory tract. |
| Aspiration Hazard | No data available |
| Medical Conditions Aggravated by Exposure | eye disorders, respiratory disorders, skin disorders, gastrointestinal disorders; May produce an allergic reaction. Persons already sensitized to diisocyanates may develop allergic reactions when using this product. |

Section 12. Ecological Information

| Component Analysis - Aquatic Toxicity | 2-Propanol, 1-chloro-, phosphate (3:1) (13674-84-5) Fish: LC50 96 h Brachydanio rerio 56.2 mg/L [static]; LC50 96 h Pimephales promelas 98 mg/L [static]; LC50 96 h Poecilia reticulata 30 mg/L [static] Algae: EC50 72 h Desmodesmus subspicatus 45 mg/L IUCLID; EC50 96 h Pseudokirchneriella subcapitata 4 mg/L IUCLID Invertebrate: EC50 48 h Daphnia magna 63 mg/L IUCLID |
|--|--|
| Bioaccumulation | No information available. |
| Mobility | No information available. |
| Biodegradation | Contains non readily biodegradable component(s). |

Section 13. Disposal

| Disposal Methods | Dispose of contents/container in accordance with local/regional/national | | |
|------------------|--|--|--|
| | /international regulations. Do not allow to enter into ground-water, surface | | |
| | water or drains. | | |

Section 14. Transport Information

| UN Number | 1950 |
|-------------------------|--|
| UN Proper Shipping Name | Aerosols |
| DOT Classification | Hazard Class: 2.2 Required Label(s): 2.2 |
| Packing Group | None assigned |

Section 15. Regulatory Information

| U.S. Federal Regulations | This material contains one or more of the following chemicals required to be identified under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), and/or require an OSHA process safety plan. Isocyanic acid, polymethylenepolyphenylene ester (9016-87-9) SARA 313: 1 % de minimis concentration SARA Section 311/312 (40 CFR 370 Subparts B and C) Acute Health: Yes Chronic Health: Yes Fire: Yes Pressure: Yes Reactivity: Yes |
|---|--|
| U.S. State Regulations | The following components appear on one or more of the following state hazardous substances lists: Isocyanic acid, polymethylenepolyphenylene ester (9016-87-9) NJ |
| | Propane (74-98-6) MA, MN, NJ, PA |
| | Isobutane (75-28-5) MA, NJ, PA |
| | Dimethyl ether (15-10-6) MA, MN, NJ, PA |
| Canadian WHMIS Ingredient Disclosure List (IDL) | Not listed under California Proposition 65 Components of this material have been checked against the Canadian WHMIS Ingredients Disclosure List. The List is composed of chemicals which must be identified on SDSs if they are included in products which meet WHMIS criteria specified in the Controlled Products Regulations and are present above the threshold limits listed on the IDL: Castor oil (8001-79-4) 1 % |
| WHMS Classification | B5, D2A, D2B |

Section 16. Other Information

| Revision Date | | 4/8/2016 |
|----------------------|---|----------|
| HMIS and NFPA Rating | HMIS Health: 2* Fire: 3 Reactivity: 3 NFPA Health: 2 | |
| | Fire: 3 Reactivity: 3 | |

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate

- 3 = Serious
- 4 = Severe
- * = Chronic hazard

Disclaimer

The data contained herein is based upon information that Soudal Accumetric believes to be reliable. Users of this product have the responsibility to determine that suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements or suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.