



# Safety Data Sheet

## BOSS® 814 Intumescent Firestop Sealant

### Section 1. Identification

Product Identifier	BOSS® 814 Intumescent Firestop Sealant		
Synonyms	81450; 81429; 81420; 81410; C39038RD; 03419RD10; 03479RD17; 03469RD10; 03471RD01		
Manufacturer Stock Numbers	C39038RD; 03419RD10; 03479RD17; 03469RD10; 03471RD01		
Recommended use	Refer to Technical Information		
Uses advised against	Refer to Technical Information		
Manufacturer Contact			
Address	Soudal Accumetric 350 Ring Road Elizabethtown, KY, 42701 USA		
	Phone	Emergency Phone	Fax
	(270) 769-3385	(800) 424-9300 CHEMTREC	(270) 765-2412

### Section 2. Hazards Identification

Classification	N/A
Signal Word	
Pictogram	
Hazard Statements	N/A
Precautionary Statements	
Response	N/A
Prevention	N/A
Storage	N/A
Disposal	N/A

General	If medical advice is needed, have product container or label at hand Keep out of reach of children Read label before use
Ingredients of unknown toxicity	0%
Hazards not Otherwise Classified	
GHS Classification	Not a hazardous substance or mixture.
GHS Label Element	Not a hazardous substance or mixture.
Other hazards	None known

### Section 3. Ingredients

CAS	Ingredient Name	Weight %
64742-46-7	Distillates (petroleum), hydrotreated middle	< 1 %
27138-31-4	Dipropylene glycol dibenzoate	1% - 5%

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First-Aid Measures

Ingestion	No first aid should be needed.
Inhalation	Remove to fresh air. If symptoms persist, obtain appropriate medical attention.
Skin Contact	Wash affected area with soap and water.
Eye Contact	Immediately flush with large amounts of water. If irritation occurs, seek medical attention.

### Section 5. Fire Fighting Measures

Suitable Extinguishing Media	Alcohol Foam, Carbon Dioxide, Dry Chemical, Foam, Water Fog
Unsuitable Extinguishing Media	None known
Unusual Fire or Explosion Hazards	Product will not burn, but may splatter if temperature exceeds boiling point of water. Dried solids can burn, giving off oxides of carbon.
Special Fire Fighting Procedures	Non-flammable (aqueous emulsion). After water evaporates, remaining material will burn. Breathing apparatus required when fighting fires in enclosed areas.

### Section 6. Accidental Release Measures

Steps to be taken in case of spill or release	Determine whether to evacuate or isolate the area according to your local emergency plan. Observe all personal protection equipment
---	---

recommendations described in Sections 5 and 8. For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. For small spills, wipe up or scrape up and contain for salvage or disposal. Clean area as appropriate since spilled material, even in small quantities, may present a slip hazard. Final cleaning may require the use of steam, solvents or detergents. Dispose of saturated absorbent or cleaning materials appropriately, since spontaneous heating may occur.

Local, state and federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which federal, state and local laws and regulations are applicable. Sections 13 and 15 of this MSDS provide information regarding certain federal and state requirements.

## Section 7. Handling and Storage

Handling	Avoid breathing vapors in top of shipping container. Keep container closed. Use with adequate ventilation. Avoid contact with skin and clothing. Wash thoroughly after handling.
Storage	Store in a cool dry place. Protect from freezing and excessive heat.

## Section 8. Exposure Controls/Personal Protection

Occupational Exposure Limits	Ingredient Name	ACGIH TLV	OSHA PEL	STEL
	Distillates (petroleum), hydrotreated middle	5 mg/m <sup>3</sup>	5 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>
	Dipropylene glycol dibenzoate	N/A	N/A	N/A
Personal Protective Equipment	Goggles			
Engineering Controls	Local Ventilation: Recommended General Ventilation: Recommended			
Ventilation	Local exhaust ventilation is recommended to maintain vapor level below TLV.			
Respiratory Protection	Use respiratory protection unless adequate exhaust ventilation is provided or exposure assessment demonstrates that exposures are within exposure guidelines. Industrial Hygiene Personnel can assist in judging the adequacy of existing engineering controls.			
	Suitable Respirator: General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits as determined by air sampling or are unknown, appropriate respiratory protection should be worn. Follow OSHA Respirator Regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators.			
Eye Protection	Chemical goggles if liquid contact is likely, or safety glasses with side shields.			
Skin Protection	Wash at mealtimes and end of shift. Contaminated clothing and shoes should be removed as soon as practical and thoroughly cleaned before reuse. Chemical protective gloves are recommended.			

Suitable Gloves:  
Silver Shield® 4H®

Note

These precautions are for room temperature handling. Use at elevated temperatures or aerosol/spray applications may require added precautions. For further information regarding aerosol inhalation toxicity, please refer to the guidance document regarding the use of silicone-based materials in aerosol applications that has been developed by the silicone industry ([www.SEHSC.com](http://www.SEHSC.com)).

## Section 9. Physical and Chemical Properties

Physical State	Paste
Color	Red
Odor	Slight
Odor Threshold	N/A
Solubility	Dilutable in wet stage
Partition coefficient Water/n-octanol	N/A
VOC%	28 g/L
Viscosity	750,000 cPs
Specific Gravity	1.38
Density lbs/Gal	N/A
Pounds per Cubic Foot	N/A
Flash Point	Not determined
FP Method	N/A
Ph	7.85
Melting Point	0C
Boiling Point	100C
Boiling Range	N/A
LEL	N/A
UEL	N/A
Evaporation Rate	Slower than n-Butyl acetate
Flammability	N/A
Decomposition Temperature	N/A
Auto-ignition Temperature	N/A
Vapor Pressure	Not determined
Vapor Density	Lighter than air

Note

The above information is not intended for use in preparing product specifications. Contact Soudal Accumetric before writing specifications.

## Section 10. Stability and Reactivity

Chemical Stability	Stable
Hazardous polymerization	Will not occur
Conditions to Avoid	None known
Materials to Avoid / Incompatibility	None known

## Section 11. Toxicological Information

Component Toxicology Information	No known applicable information.
Special Hazard Information on Components	No known applicable information.

## Section 12. Ecological Information

Environmental Effects	Complete information is not yet available.
Environmental Fate and Distribution	Complete information is not yet available.
Fate and Effects in Waste Water Treatment Plants	Complete information is not yet available.

## Section 13. Disposal

Waste Disposal Method	We make no guarantee or warranty of any kind that the use or disposal of this product complies with all local, state, or federal laws. It is also the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable statutes.
-----------------------	---

This product is not known to be regulated under RCRA regulations. Disposal of unused portions of this product and process waste containing this product should be done only after a careful evaluation and in compliance with all federal, local and state laws.

## Section 14. Transport Information

UN Number	N/A
UN Proper Shipping Name	Not regulated
DOT Classification	Not regulated
Packing Group	Not regulated
Air Shipment (IATA)	Not subject to IATA regulations.
Ocean Shipment (IMDG)	Not subject to IMDG code.
Road Shipment Information (DOT)	Not subject to DOT regulations.

## Section 15. Regulatory Information

TSCA Status	All chemical substances found in this product comply with the Toxic Substances Control Act inventory reporting requirements.
SARA Title III Section 302 Extremely Hazardous Substances	None
SARA Titre III Section 304 CERCLA Substances dangereuses	None
SARA Title III Section 312 Hazard Class	Acute: Yes Chronic: No Fire: No Pressure: No Reactive: No
SARA Title III Section 313 Toxic Chemicals	None present or none present in regulated quantities.
California Proposition 65	This product contains the following chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm: None known

<b>Section 16. Other Information</b>
--------------------------------------

Revision Date	8/12/2016
Disclaimer	The data contained herein is based upon information that Soudal Accumetric believes to be reliable. Users of this product have the responsibility to determine that suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements or suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.